



Hyperion Fluorescein

Valeport's Hyperion Fluorometer sensor range delivers high performance measurements of Chlorophyll a, Phycocyanin, Fluorescein (Uranine), or Rhodamine in a compact & robust package ideal as a standalone sensor, for ROV and AUV integration or used with as part of a multi-sensor array and data logger.

Offered as standard in a 6000m depth rated, titanium housing the Hyperion Fluorometer has a wide range (9-28V DC) isolated power supply, data output up to 16Hz and RS232, RS485 and Modbus communications.

Hyperion Fluorometers can be supplied in a more rugged form that includes Acetal protection rings, a shaped anti-snag connector cover and a Kevlar weave protected cable.

DATA SHEET

Product Details



OPTICAL



DATALOG X2
& ENVIROLOG
SOFTWARE

Valeport Limited
St. Peter's Quay, Totnes,
Devon TQ9 5EW United Kingdom

Telephone: +44 (0) 1803 869292
Email: sales@valeport.co.uk
www.valeport.co.uk



Sensor Specification	
Fluorescein*	
Excitation	470 nm
Detection	545 nm
Dynamic Range:	0-500 ppb
Minimum Detection (3x SD in RO water)	0.01 ppb
Linearity	0.99 R2
Response Time	0.03 - 2 sec
Output Rate	0.5 Hz - 16 Hz (free running) software controlled

* Calibrated against Fluorescein/Rhodamine solution

Communications	
The instrument will operate in real time, with set up performed by direct communications with a PC before and after deployment.	
RS232/RS485/ Modbus RTU	Up to 200m cable Direct to serial port via USB adapter
Baud Rate	2400 - 115200
Protocol	8 data bits, 1 stop bit, No parity, No flow control

Electrical	
External	9 – 28V DC Isolated
Power	<600mW
Connector	SubConn MCBH6F

Software	
Valeport supply DataLog X2 Windows software for instrument setup, data download and display.	

Physical	
Materials	Titanium with Sapphire glass window
Depth Rating	6,000m
Dimensions	40mmØ x 179.5mm (including connector)
Weight	0.50 kg (in air)
	0.26 kg (in water)
Operating Temp	-5°C - 35°C (the sensor is damaged above 60°C)
Ordering	
0901001 - F	Fluorescein (Uranine)

Supplied with:
 · 1x Hyperion Instrument
 · 1x 0.5m pig tail
 · Manual and transit case
 · DataLog X2 Software

Datasheet Reference: Hyperion Fluorometer | April 2020

As part of our policy of continuing development, Valeport Ltd. reserve the right to alter at any time, without notice, all prices, specifications, designs and conditions of sale of all equipment - Valeport Ltd © 2020

